



- Unidirectional electret condenser cardioid microphone element.
- 64 selectable channels.
- Maximum input level: 126 dB SPL.
- Dynamic range: 95 dB or more.
- ON/OFF switch prevents the microphone from rolling.
- WB-2000 rechargeable battery or Single AA battery operation for compact and lightweight body.
- Low-battery indicator (Sufficient power/Green, Low battery/Dimming green, Empty/Red).
- Built-in antenna.



TECHNICAL DATA

- Microphone Element** Electret condenser microphone unit: Unidirectional
- Modulation:** Frequency modulation
- Frequency Range:** 576 –932 MHz*, UHF
- Channel Selectable:** 64 channels (the number of channels may differ from country to country.)
- RF Carrier Power:** 50 mW or less
- Tone Frequency:** 32.768 kHz
- Oscillator:** PLL synthesizer
- Maximum Input Level:** 126 dB SPL
- Maximum Deviation:** ±40 kHz
- Audio Frequency Response:** 100Hz – 15kHz
- Dynamic Range (AF Circuit):** 95dB or more (with WT-5800)
- Battery:** WB-2000 rechargeable battery (option) or AA alkaline dry cell battery
- Battery Life:** Approx. 13h (when the WB-2000 rechargeable battery is Used)
Approx. 10h (when the alkaline battery is used))
- Indicator:** Power/Battery lamps
- Antenna:** Built-in type
- Operating Temperature:** -10°C to +50°C (14°F to 122°F) (except battery)
- Operating Humidity 30% to 85% RH (no condensation)
- Finish:** Resin, coating
- Dimensions:** $\phi 43.6 \times 231.5$ mm ($\phi 1.72'' \times 9.11''$)
- Weight:** 180 g (0.4 lb) (with battery)
- Accessory:** Microphone holder W3/8" (with stand adapter)

