



- Multifrequency microphone system.
- True diversity system.
- 80 selectable UHF channels (863-865 MHz).
- ACT function for transmitting the selected frequency to the pocket transmitter via infrared signal.
- Autoscans.
- Volume and squelch controls.
- Gain can be adjusted at the pocket transmitter.
- Indication for channel, antenna A/B, ACT status and AF audio level (receiver), channel and battery status (pocket transmitter).
- Robust metal housing (receiver).

### TECHNICAL DATA

- Carrier frequency:** 863-865 MHz
- Transmitting power:** < 10 mW (EIRP)
- RF S/N ratio:** 105 dB
- Audio range:** 50-18,000 Hz, ±3 dB
- Dynamic range:** 120 dB
- THD:** < 0.5 %
- Audio output:** 350 mV/10 kΩ (jack) 25 mV/10 kΩ (XLR, bal.)
- Operating range:** Approx. 30 m
- Admiss. ambient temp:** 0-40 °C
- Power supply:** (Transmitter) 2 x 1.5 V batt. AA size
- Receiver:** via suppl. plug-in PSU
- Dimensions:** (Transmitter) 62x105x25 mm (Receiver) 152x38x120 mm
- Weight:** (Transmitter) 88 g (Receiver) 482 g
- Connections:** 1 x 6.3 mm jack, unbal. 1 x XLR, bal.

